



## TeleControl Serie 21 , 2 Botones , 1 Velocidad, Alcance 100Mts 12V DC

### Características Esenciales


- 1 Años de Garantía, Servicio y Atención al Cliente en Chile

## Especificaciones Técnicas

<b>Codigo FCC</b>	2ASYP-VR8	<b>Rango de Frecuencia</b>	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
<b>Fuente de Alimentación del Transmisor</b>	2 AA batteries	<b>Parada de Emergencia</b>	No
<b>Material</b>	Glass-Fiber PA	<b>Rango de temperatura de Trabajo</b>	-40 ~ 185 °F / -40 ~ 85°C
<b>Distancia de Control</b>	Up to 180 ft	<b>Normas</b>	FCC and OSHA standard 1910.179
<b>Código de Seguridad</b>	32 bits (4.3 billion)	<b>Garantía</b>	1 Year
<b>Potencia del Transmisor</b>	≤10dBm		

### F21-2S/2D TRANSMITTER

Small, economical, convenient



MODEL: F21-2S-TX  
 ITEM CODE: 921-002-001  
 Dimensions: 132 x 45 x 28 mm  
 Weight: 98g (without batteries)

- Product Features:**
- Two single/double speed buttons, one "STOP"
  - 6 control contacts.
  - With battery voltage warning device, the power supply is cut off during low power
  - Safety key switch to prevent from unauthorized user
  - Program the button function by computer interface.
  - Up/Down can be programmed to interlock or non-interlock.
  - The spare button can be programmed to start, toggle or normal, etc.

**Transmitter Parameters: F21-2S**

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ + 85° C
Control distance	Approx 60m (100 meters is customized)

- Standard Configuration:**
- One transmitter (with hanging belt)
  - One dust bag
  - One receiver
  - Receiver with 1.6 meter cable
  - Battery: One pair
  - One receiver antenna.
  - Operation and maintenance manual.

- Safety features:**
- Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the connect control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certified.



### F21-2S/2D RECEIVER



MODEL: F21-2S-RXC  
 ITEM CODE: 921-103-011  
 Dimensions: 88 x 92 x 62 mm  
 Weight: 320g



**Transmitter Parameters: F21-RXC**

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	12~30V AC/DC; 65~440V AC/DC (optional)
Output contactor capacity	BA sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 60m (100 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ + 85° C



**Application:**  
 Single-hook, single-speed electric hoist or hoist-type traffic and industrial remote control with 8 contacts or less.

## Peso & Dimensiones

<b>Peso Total</b>	1 lbs / 1 Kg
<b>Paquete 1 Peso Neto</b>	1 lbs / 0 Kg
<b>Paquete 1 Ancho</b>	2 in / 5.08 cm
<b>Paquete 1 Peso Bruto</b>	1 lbs / 0 Kg
<b>Paquete 1 Altura</b>	5 in / 12.7 cm
<b>Paquete 1 Profundidad</b>	1 in / 2.54 cm

## Detalles del Empaque

Referential Images / Imágenes Referenciales

Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso