



TeleControl Serie 21 , 2 Botones , 1 Velocidad, Alcance 100Mts 18 a 65V AC DC

Características Esenciales


- 3 Años de Garantía, Servicio y Atención al Cliente en Chile

Especificaciones Técnicas

Codigo FCC	OFNF21	Potencia del Transmisor	≤10dBm
Fuente de Alimentación del Transmisor	2 AA batteries	Rango de Frecuencia	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Material	Glass-Fiber PA	Protección IEC Motor	IP65
Distancia de Control	Approx 60m (100 meters is customized)	Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C
Código de Seguridad	32 bits (4.3 billion)	Garantía	3 Year

F21-2S/2D TRANSMITTER

Small, economical, convenient



MODEL: F21-2S-TX
ITEM CODE: 921-002-001
Dimensions: 132 x 45 x 28 mm
Weight: 98g (without batteries)

- Product Features:**
- Two single/double speed buttons, one "STOP"
 - 6 control contacts.
 - With battery voltage warning device, the power supply is cut off during low power
 - Safety key switch to prevent from unauthorized user
 - Program the button function by computer interface.
 - Up/Down can be programmed to interlock or non-interlock.
 - The spare button can be programmed to start, toggle or normal, etc.

Transmitter Parameters: F21-2S	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ + 85° C
Control distance	Approx 60m (100 meters is customized)

- Standard Configuration:**
- One transmitter (with hanging belt)
 - One dust bag
 - One receiver
 - Receiver with 1.6 meter cable
 - Battery: One pair
 - One receiver antenna.
 - Operation and maintenance manual.

- Safety features:**
- Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certified.



F21-2S/2D RECEIVER



MODEL: F21-2SRXC
ITEM CODE: 921-103-011
Dimensions: 88 x 92 x 62 mm
Weight: 320g



Transmitter Parameters: F21-RXC	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~30V AC/DC; 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 60m (100 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ + 85° C



Application:
 Single-hook, single-speed electric hoist or hoist-type traffic and industrial remote control with 8 contacts or less.

Peso & Dimensiones

Peso Total 1 lbs / 1 Kg

Detalles del Empaque

Paquete 1 Peso Neto 1 lbs / 0 Kg

Paquete 1 Ancho 7 in / 17.78 cm

Paquete 1 Peso Bruto 1 lbs / 0 Kg

Paquete 1 Altura 9 in / 22.86 cm

Paquete 1 Profundidad 3 in / 7.62 cm

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso