



TeleControl Serie 21 , 4 Botones , 2 Velocidades, Alcance 100Mts

Características Esenciales

- 1 Años de Garantía, Servicio y Atención al Cliente en Chile

Especificaciones Técnicas

Codigo FCC	OFNF21	Rango de Frecuencia	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Fuente de Alimentación del Transmisor	2 AA batteries	Parada de Emergencia	Yes
Material	Glass-Fiber PA	Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C
Distancia de Control	300 ft up to 600 ft with optional antenna	Normas	FCC and OSHA standard 1910.179
Código de Seguridad	32 bits (4.3 billion)	Garantía	1 Year
Potencia del Transmisor	≤10dBm		

F21-4S/4D TRANSMITTER

Economical, safe, convenient



MODEL: F21-4S-TX
ITEM CODE: 921-004-001
Dimensions: 156 x 61 x 51 mm
Weight: 255g (without batteries)

- Product Features:**
- 4 buttons (D means double steps), spare button
 - 8 control contacts.
 - With battery voltage warning device, the power supply is cut off during low power.
 - Program the button function by computer interface.
 - Up/Down, East/West can be programmed to interlock or non-interlock.
 - The spare button can be programmed to start, toggle or normal, etc.

- Standard Configuration:**
- One transmitter (with hanging belt)
 - One dust bag
 - One receiver
 - Receiver with 1.6 meter cable
 - Battery: One pair
 - One receiver antenna.
 - Operation and maintenance manual.


Transmitter Parameters: F21-TX

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ +85° C
Control distance	Approx 100m (200 meters is customized)

Safety features:
Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certified.



Start protection circuit
Each system has a dedicated testing circuit. Before the system starts, the transmitting system tests all switch contacts and receiving system tests relays. Only if both procedures are passed the whole system starts working.



MODEL: F21-RXC
ITEM CODE: 921-100-112
Dimensions: 205 x 86 x 80 mm
Weight: 620 g



Transmitter Parameters: F21-XRC

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 100m (200 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ +85° C



Connect buckle



Damping rubber



Safety Code

Application:
Single-hook, single-speed electric hoist or hoist-type traffic and industrial remote control with 8 contacts or less.

Peso & Dimensiones

Peso Total 4 lbs / 2 Kg

Detalles del Empaque

Paquete 1 Peso Neto 4 lbs / 2 Kg

Paquete 1 Ancho 8 in / 20.32 cm

Paquete 1 Peso Bruto 4 lbs / 2 Kg

Paquete 1 Altura 2 in / 5.08 cm

Paquete 1 Profundidad 12 in / 30.48 cm

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso