



## TeleControl Serie 21 , 4 Botones , 2 Velocidades, Alcance 100Mts

### Características Esenciales

- 3 Años de Garantía, Servicio y Atención al Cliente en Chile

## Especificaciones Técnicas

<b>Codigo FCC</b>	OFNF21	<b>Potencia del Transmisor</b>	≤10dBm
<b>Fuente de Alimentación del Transmisor</b>	2 AA batteries	<b>Rango de Frecuencia</b>	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
<b>Material</b>	Glass-Fiber PA	<b>Protección IEC Motor</b>	IP65
<b>Distancia de Control</b>	Approx 100m (200 meters is customized)	<b>Rango de temperatura de Trabajo</b>	-40 ~ 185 °F / -40 ~ 85°C
<b>Código de Seguridad</b>	32 bits (4.3 billion)	<b>Garantía</b>	3 Year

### F21-4S/4D TRANSMITTER

Economical, safe, convenient



MODEL: F21-4S-TX  
ITEM CODE: 921-004-001  
Dimensions: 156 x 61 x 51 mm  
Weight: 255g (without batteries)

- Product Features:**
- 4 buttons (D means double steps), spare button
  - 8 control contacts.
  - With battery voltage warning device, the power supply is cut off during low power.
  - Program the button function by computer interface.
  - Up/Down, East/West can be programmed to interlock or non-interlock.
  - The spare button can be programmed to start, toggle or normal, etc.

- Standard Configuration:**
- One transmitter (with hanging belt)
  - One dust bag
  - One receiver
  - Receiver with 1.6 meter cable
  - Battery: One pair
  - One receiver antenna.
  - Operation and maintenance manual.


**Transmitter Parameters: F21-TX**

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ +85° C
Control distance	Approx 100m (200 meters is customized)

**Safety features:**  
Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certified.



**Start protection circuit**  
Each system has a dedicated testing circuit. Before the system starts, the transmitting system tests all switch contacts and receiving system tests relays. Only if both procedures are passed the whole system starts working.



MODEL: F21-RXC  
ITEM CODE: 921-100-112  
Dimensions: 205 x 86 x 80 mm  
Weight: 620 g



**Transmitter Parameters: F21-XRC**

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 100m (200 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C ~ +85° C



Connect buckle



Damping rubber



Safety Code

**Application:**  
Single-hook, single-speed electric hoist or hoist-type traffic and industrial remote control with 8 contacts or less.

## Peso & Dimensiones

**Peso Total** 4 lbs / 2 Kg

## Detalles del Empaque

**Paquete 1 Peso Neto** 4 lbs / 2 Kg

**Paquete 1 Ancho** 8 in / 20.32 cm

**Paquete 1 Peso Bruto** 4 lbs / 2 Kg

**Paquete 1 Altura** 2 in / 5.08 cm

**Paquete 1 Profundidad** 12 in / 30.48 cm

Referential Images / Imágenes Referenciales  
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso