



## TeleControl Serie 21 , 6 Botones Alcance 100Mts

### Características Esenciales

- 3 Años de Garantía, Servicio y Atención al Cliente en Chile

## Especificaciones Técnicas

Codigo FCC	OFNF21	Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C
Código de Seguridad	32 bits (4.3 billion)	Garantía	3 Year



**MODEL: F21-E2**  
**ITEM CODE: 921-006-002**  
**Dimensions: 156 x 61 x 51 mm**  
**Weight: 255g (without batteries)**

- Product Features:**
- 8 operation buttons, 6 single-speed buttons and "STOP"
  - 8 control contacts.
  - With battery voltage warning device, the power supply is cut off during low power.
  - Program the button function by computer interface.
  - Up/Down, East/West, North/South can be programmed to interlock or non-interlock.
  - The spare button can be programmed to start, toggle or normal, etc.


- Standard Configuration:**
- One transmitter (with hanging belt)
  - One dust bag
  - One receiver
  - Receiver with 1.6 meter cable
  - Battery: One pair
  - Operation and maintenance manual.

Transmitter Parameters: F21-TX	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → 85° C
Control distance	Approx 100m (200 meters is customized)

- Standard Configuration:**
1. Unique 32 bits ID Code
  2. Hamming code
  3. Enhanced watch-dog circuit
  4. With FCC and CE certificate



**Start protection circuit**  
 Each system has a dedicated testing circuit. Before the system starts, the transmitting system tests all switch contacts and receiving system tests relays. Only if both procedures are passed the whole system starts working.



**MODEL: F21-RXC**  
**ITEM CODE: 921-100-112**  
**Dimensions: 205 x 86 x 80 mm**  
**Weight: 620 g**



Transmitter Parameters: F21-TX	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 100m (200 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → 85° C



Connect buckle



Damping rubber



Safety Code

**Application:**  
 Single-hook, single-speed electric hoist or hoist-type traffic and industrial remote control with 8 contacts or less.

## Peso & Dimensiones

**Peso Total** 4 lbs / 2 Kg

## Detalles del Empaque

**Paquete 1 Peso Neto** 5 lbs / 2 Kg

**Paquete 1 Ancho** 8 in / 20.32 cm

**Paquete 1 Peso Bruto** 4 lbs / 2 Kg

**Paquete 1 Altura** 13 in / 33.02 cm

**Paquete 1 Profundidad** 12 in / 30.48 cm

Referential Images / Imágenes Referenciales  
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso