



TeleControl Serie 24 , 12 Botones , 1 Velocidad, Alcance 100Mts

Características Esenciales

- 3 Años de Garantía, Servicio y Atención al Cliente en Chile

Especificaciones Técnicas

Codigo FCC	OFNF21	Potencia del Transmisor	≤10dBm
Fuente de Alimentación del Transmisor	2 AA batteries	Rango de Frecuencia	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Material	Glass-Fiber PA	Protección IEC Motor	IP65
Distancia de Control	Approx 100m (200 meters is customized)	Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C
Código de Seguridad	32 bits (4.3 billion)	Garantía	3 Year



MODEL: F24-12S
ITEM CODE: 24-012-001
 Dimensions: 186 x 61 x 51 mm
 Weight: 280g (without batteries)

- Product Features:**
- 7-12 buttons (D means double steps), STOP, START, spare buttons
 - Up to 20 control contacts.
 - With battery voltage warning device, the power supply is cut off during low power.
 - Safety switch key to prevent from unauthorized user.
 - Program the button function by computer interface.
 - Up/Down, East/West, North/South can be programmed to interlock or non-interlock.
 - Power key can be programmed to start, toggle switch, normal or other functions.
 - The spare buttons can be programmed to normal, interlock, toggle or start, etc.

Transmitter Parameters: F24-12S	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → +85° C
Control distance	Approx 100m (200 meters is customized)

- Standard Configuration:**
- One transmitter (with hanging belt)
 - One dust bag
 - One receiver
 - Receiver with 1.6 meter cable
 - Battery: One pair
 - One receiver antenna
 - Operation and maintenance manual.

Safety features:
 Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



F24 series remote control system have 80 channels in its frequency range. Even in situations where many sets of remote control are used in the same time, working channel can be easily chosen without interfering with other signals and hundred-percent safe reliable. With advanced design and high quality components, the system is durable and easy to operate. It can easily adapt to complicated and harsh industrial environments such as extra-high/low temperature, dusty, strong vibration, greasy, heavy humidity, etc.

Transmitter and receiver have many functions used in conjunction. The emergency stop button is located in the upper left of the transmitter which meets the safety and ergonomics. When stop button is pressed, the system stops working immediately and unconditionally. Transmitter is equipped with a shell of more consistent with ergonomics. The new shell material is more durable, lighter and thinner.

MODEL: F24-RXC
ITEM CODE: 924-100-102-112
 Dimensions: 210 x 162 x 107 mm
 Weight: 1220g



Transmitter Parameters: F24-RXC	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 100m (200 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → +85° C



Connect buckle



Damping rubber



Safety Code

Application:
 The heavy industrial machinery, such as lifting machinery, crane, hydraulic crane, concrete pump, roller coaster, mining machinery, hoist, truck crane, dump truck, lifting locomotive, lifting machine, etc.

Peso & Dimensiones

Peso Total 6 lbs / 3 Kg

Detalles del Empaque

Paquete 1 Peso Neto 6 lbs / 3 Kg

Paquete 1 Ancho 9 in / 22.86 cm

Paquete 1 Peso Bruto 6 lbs / 3 Kg

Paquete 1 Altura 5 in / 12.7 cm

Paquete 1 Profundidad 18 in / 45.72 cm

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso