



TeleControl Serie 24 , 6 Botones , 2 Velocidades, Alcance 100Mts

Características Esenciales

- 3 Años de Garantía, Servicio y Atención al Cliente en Chile

Especificaciones Técnicas

| | | | |
|--|--|--|--------------------------------------|
| Codigo FCC | OFNF21 | Potencia del Transmisor | ≤10dBm |
| Fuente de Alimentación del Transmisor | 2 AA batteries | Rango de Frecuencia | VHF: 310~331 MHz; UHF: 425 ~ 446 MHz |
| Material | Glass-Fiber PA | Protección IEC Motor | IP65 |
| Distancia de Control | Approx 100m (200 meters is customized) | Rango de temperatura de Trabajo | -40 ~ 185 °F / -40 ~ 85°C |
| Código de Seguridad | 32 bits (4.3 billion) | Garantía | 3 Year |



MODEL: F24-6D
ITEM CODE: 924-006-001
Dimensions: 156 x 61 x 51 mm
Weight: 255g (without batteries)

- Product Features:**
- 7-12 buttons (0 means double steps), STOP, START, spare buttons
 - Up to 20 control contacts.
 - With battery voltage warning device, the power supply is cut off during low power.
 - Safety switch key to prevent from unauthorized user.
 - Program the button function by computer interface.
 - Up/Down, East/West, North/South can be programmed to interlock or non-interlock.
 - Power key can be programmed to start, toggle switch, normal or other functions.
 - The spare buttons can be programmed to normal, interlock, toggle or start, etc.

Transmitter Parameters: F24-6D

| | |
|----------------------------|--|
| Material | Glass-Fiber PA |
| Enclosure protection class | IP65 |
| Frequency range | VHF: 310~331MHz; UHF: 425~446MHz |
| Transmitter power | < 10dBm |
| Transmitter power supply | 2 AA batteries |
| Safety code | 32 bits (4.3 billion) |
| Temperature range | -40° C → 85° C |
| Control distance | Approx 100m (200 meters is customized) |

- Standard Configuration:**
- One transmitter (with hanging belt)
 - One dust bag
 - One receiver
 - Receiver with 1.6 meter cable
 - Battery: One pair
 - One receiver antenna
 - Operation and maintenance manual.

Safety features:
 Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certified.



F24 series remote control system have 80 channels in its frequency range. Even in situations where many sets of remote control are used in the same time, working channel can be easily chosen without interfering with other signals and hundred-percent safe reliable. With advanced design and high quality components, the system is durable and easy to operate. It can easily adapt to complicated and harsh industrial environments such as extra-high/low temperature, dusty, strong vibration, greasy, heavy humidity, etc.

Transmitter and receiver have many functions used in conjunction. The emergency stop button is located in the upper left of the transmitter which meets the safety and ergonomics. When stop button is pressed, the system stops working immediately and unconditionally. Transmitter is equipped with a shell of more consistent with ergonomics. The new shell material is more durable, lighter and thinner.

MODEL: F24-RXC
ITEM CODE: 924-100-102-112
Dimensions: 210 x 162 x 107 mm
Weight: 1220g



Transmitter Parameters: F21-TX

| | |
|----------------------------|--|
| Material | Glass-Fiber PA |
| Enclosure protection class | IP65 |
| Frequency range | VHF: 310~331MHz; UHF: 425~446MHz |
| Receiver sensitivity | -130dBm |
| Receiver power supply | 38~50V AC/DC, 65~440V AC/DC (optional) |
| Output contactor capacity | 8A sealed relay output (with AC 250V/10A relays, 10A fuse) |
| Control distance | Approx 100m (200 meters is customized) |
| Safety code | 32 bits (4.3 billion) |
| Temperature range | -40° C → 85° C |



Application:
 The heavy industrial machinery, such as lifting machinery, crane, hydraulic crane, concrete pump, roller coaster, mining machinery, hoist, truck crane, dump truck, lifting locomotive, lifting machine, etc.

Peso & Dimensiones

Peso Total 6 lbs / 3 Kg

Detalles del Empaque

Paquete 1 Peso Neto 4 lbs / 2 Kg

Paquete 1 Ancho 9 in / 22.86 cm

Paquete 1 Peso Bruto 6 lbs / 3 Kg

Paquete 1 Altura 5 in / 12.7 cm

Paquete 1 Profundidad 18 in / 45.72 cm

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso