

1 ton Electric Chain Hoist w/ Power Trolley 1 Speed 110V 1Ã, 60HZ 20ft G100 Nickel Duty H2/M3



Especificaciones Técnicas

Capacidad de Carga	1 ton	Caidas de Cadena	2
Voltaje	1 Phase 110~120V 60Hz	Longitud de cadena	40
Numero de Velocidades	1 Speed	Load Chain weight per foot [lbs]	0.73
Numero de Velocidades	Variable Speed	Humedad	20%~90%
Hoist Contactors Amps	25A	Temperatura	-4 ~ 104° F / -20 ~ 40° C
Hoist Contactor Coil Voltage	24 V	Tipo Transmisión / Reductor	Spur gearbox
IEC Hoist IP Protection	IP55	Reducer Lubrication Type	Oil
Protección IEC Motor	IP55	Paint Specifications	Electrostatic Sprayed Plastic (ESP) Epoxy resins, Polyester Resins, Barium, Pigments
Pendant Control Yes No	Yes	Normas	ASME HST-1 , ASME B30.16 , B30.17 , EN60204-35
IEC Pendant Control Protection	IP66	Standards Certified	CE
Pendant Control Emergency Stop	Yes	Potencia del Trolley	500
Pendant Control total Length	17 ft	Cantidad de Velocidades	1
Hoist Motor Power in KW	0,75	Trolley Motor Insulation Grade	F
Hoist Motor Insulation Grade	F	Trolley Contactors Coil Voltage	24 V
Potencia Total Watts	750	Trolley Wheel Diameter	95
Power Cord Length and Phase Order	3 ft / Black L1, White, Green ground	Trolley Wheel Material	No. 45 steel
Optional Load Chain Brand & Country of Origin	FEC Japan or RUD Germany	Trolley Minimum Turn Radius	1,3
Tipo de Cadena	G100 Nikel	Trolley Beam Range	2" to 6"
Dimensiones de la Cadena	7.1 mm	Trolley Beam Extension Kit	up to 12"

Peso & Dimensiones

A Altura Total	560
J Boca Gancho	59
W Ancho	420
H Altura Muerta	645
D Depth	695
1st Package Type	Wood Crate
Peso Total (sin cable o cadena)	72.07
2nd Package Type	Wood Crate
Peso Total	308 lbs / 140 Kg

Detalles del Empaque

Paquete 1 Altura	26 in / 66.04 cm
Paquete 2 Altura	23 in / 58.42 cm
Paquete 1 Ancho	16 in / 40.64 cm
Paquete 2 Ancho	14 in / 35.56 cm
Paquete 1 Profundidad	26 in / 66.04 cm
Paquete 2 Profundidad	11 in / 27.94 cm
Paquete 1 Peso Neto	101,64 lbs / 46 Kg
Paquete 2 Peso Neto	89,1 lbs / 40 Kg
Paquete 1 Peso Bruto	209 lbs / 95 Kg
Paquete 2 Peso Bruto	99 lbs / 45 Kg

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso